

OKSI OP305VXL ECO

712A628



Undercounter unit for cooling beer

SPECIFICATION

Refrigerant: R 134a
Evaporator: Copper
Ref. System: Capillary
Circulation Pump: 6 m
Control type : Mechanical
Condenser: Air - steel construction
Casing: PVC coated steel
Colour: Gray 721MN

NUMBER OF COILS

- Beer coils - 5x (8/7 x 10m)

TECHNICAL DATA

Kompresor	12,11 cc
Compressor	
Kompresor	
Kapacitet hlađenja	
Cooling power	689 W 2460 kJ/h
Kühlleistung	
Kontinuirano istakanje	
Continuing capacity	65 l / 33 l
Zapfkapazität kontinuierlich	
Temperatura*	
Temperature*	Δ t = 10°C/20°C
Temperatur*	
Zaliha leda	
Ice bank	15 kg = 5023 kJ = 133 l / 67 l
Eisbank	
Kapacitet istakanja na 1.sat	
Cooling capacity 1. st hour	198 l / 100 l
Kühlleistung 1.Std	
Volumen kupke	
Water tank capacity	40 l
Volumen des Wasserbeckens	
Masa	
Weight	39,50 kg
Gewicht	
Širina	
Widht	450
Breite	
Dubina	
Depth	460
Tiefe	
Visina	
Height	715
Höhe	

TECHNICAL ELECTRIC SPECS

Voltage/Frequency: 230 V 50 Hz
Power: 0,65 kW
Run: 3,3 A

All specifications (data) about compressors are based on: condensing temperature (Tcond=55°C), evaporating temperature (Tev=-5°C), ambient temperature (Tamb.=32°C) and relative humidity 65±5%. All capacities and dispense rates are for 32°C Ambient, 15/24°C beer ingoing and dispensing temperature 3-5°C.

OPREMA d.d. reserves the right to modify at any time the technical data and specifications reported herein, as the result of technical updating and improvement.