

OKSI OP506VXXL ECO

712A629



Undercounter unit for cooling beer

SPECIFICATION

Refrigerant: R 134a
Evaporator: Copper
Ref. System: Capillary
Circulation Pump: 8 m
Control type : Mechanical
Condenser: Air - steel construction
Casing: PVC coated steel
Colour: Gray N14

NUMBER OF COILS

- Beer coils - 6x (8/7 x 15m)

TECHNICAL DATA

Kompresor	
Compressor	17,69 cc
Kompresor	
Kapacitet hlađenja	
Cooling power	870 W 3107 kJ/h
Kühlleistung	
Kontinuirano istakanje	
Continuing capacity	82 l / 41 l
Zapfkapazität kontinuierlich	
Temperatura*	
Temperature*	$\Delta t = 10^{\circ}\text{C}/20^{\circ}\text{C}$
Temperatur*	
Zaliha leda	
Ice bank	26 kg = 8707 kJ = 231 l / 115 l
Eisbank	
Kapacitet istakanja na 1.sat	
Cooling capacity 1. st hour	313 l / 156 l
Kühlleistung 1.Std	
Volumen kupke	
Water tank capacity	70 l
Volumen des Wasserbeckens	
Masa	
Weight	53,5 kg
Gewicht	
Širina	
Widht	520
Breite	
Dubina	
Depth	530
Tiefe	
Visina	
Height	800
Höhe	

TECHNICAL ELECTRIC SPECS

Voltage/Frequency:	230 V 50 Hz
Power:	0,62 kW
Run:	3,95 A

All specifications (data) about compressors are based on: condensing temperature (Tcond=55°C), evaporating temperature (Tev=-5°C), ambient temperature (Tamb.=32°C) and relative humidity 65±5%. All capacities and dispense rates are for 32°C Ambient, 15/24°C beer ingoing and dispensing temperature 3-5°C.

OPREMA d.d. reserves the right to modify at any time the technical data and specifications reported herein, as the result of technical updating and improvement.