

CLASSIC PET KEG (BROWN)

SPECIFICATIONS OF THE PRODUCT

Rkeg

Cycle	One way
Volume	30L
Overall dimensions Rkeg 30L	D x H = 290 x 585 mm
Weight (empty, with pressure)	425 g
Transportation pressure	0,5-2 Bar
Working pressure	3,0 Bar max
Burst pressure of the safety valve	6.5 Bar
Fitting type	A, G

Safety

PET-keg balloon material	High viscosity PET
Colour	Brown
Preform weight	425 g
Fitting	Body, basket, piston, ring plate: Polyoxymethylene Sealing ring: Thermoplastic elastomer Sealing cuff: Thermoplastic elastomer Spring: Stainless steel Colour: Body - white, Basket - white, Piston - turquoise Ring plate - turquoise, Sealing cuff - blue, grey, Sealing ring - black, Spring - metallic Reliable lock protecting against unauthorized opening Threaded design to ensure a reliable impermeability Safe recycling with the new pressure-relief cap It is easy to relieve pressure - just put the cap onto the fitting until it clicks

Limit of the bursting pressure	Over 7 bar
Rkeg structure	It withstands falling over a height of 1.2 m and at an angle 45 degrees It does not burst if alkali gets on Rkeg, but can have stress cracking It does not burst if the side wall is punctured with a sharp object at the operating internal pressure
Transport and storage temperature	From -25°C to + 30°C

Recommended when transporting / warehousing:

Rkeg 30 L	2 tiers / 4 tiers
-----------	-------------------

Rkeg function

Products	Beer, Cider, Kvass, Lemonade, Wine, Champagne
Expiration date	6 months
Bottling line	Manual bottling Automatic and semi-automatic lines for bottling to PET keg On lines designed for bottling to metallic kegs through an adapter
Bottling installation	Compatible with standard bottling systems
Recycling	100% (does not contain additives)

*We offer comprehensive solutions for Rkeg delivery and equipment from our partners (including modernising of the existing) for blow moulding and bottling

CLASSIC PET KEG (BROWN)

SPECIFICATIONS OF THE PRODUCT

Rkeg

Cycle	One way
Volume	30L
Overall dimensions Rkeg 30L	D x H = 290 x 585 mm
Weight (empty, with pressure)	425 g
Transportation pressure	0,5-2 Bar
Working pressure	3,0 Bar max
Burst pressure of the safety valve	6,5 Bar
Fitting type	A, G

Safety

PET-keg balloon material	High viscosity PET
Colour	Brown
Preform weight	425 g
Fitting	Body, basket, piston, ring plate: Polyoxymethylene Sealing ring: Thermoplastic elastomer Sealing cuff: Thermoplastic elastomer Spring: Stainless steel Colour: Body - white, Basket - white, Piston - turquoise Ring plate - turquoise, Sealing cuff - blue, grey, Sealing ring - black, Spring - metallic Reliable lock protecting against unauthorized opening Threaded design to ensure a reliable impermeability Safe recycling with the new pressure-relief cap It is easy to relieve pressure - just put the cap onto the fitting until it clicks

Limit of the bursting pressure	Over 7 bar
Rkeg structure	It withstands falling over a height of 1.2 m and at an angle 45 degrees It does not burst if alkali gets on Rkeg, but can have stress cracking It does not burst if the side wall is punctured with a sharp object at the operating internal pressure
Transport and storage temperature	From -25°C to + 30°C

Recommended when transporting / warehousing:

Rkeg 30 L	2 tiers / 4 tiers
-----------	-------------------

Rkeg function

Products	Beer, Cider, Kvass, Lemonade, Wine, Champagne
Expiration date	6 months
Bottling line	Manual bottling Automatic and semi-automatic lines for bottling to PET keg On lines designed for bottling to metallic kegs through an adapter
Bottling installation	Compatible with standard bottling systems
Recycling	100% (does not contain additives)

*We offer comprehensive solutions for Rkeg delivery and equipment from our partners (including modernising of the existing) for blow moulding and bottling